

# TAYLOR-SEIDENBACH, INC.

FAX (504) 486-7477      PHONE (504) 486-7474  
FIBERGLASS PRODUCTS -- ROOFING AND INSULATION -- HVAC PRODUCTS  
AIR FILTERS -- FIRE STOP CAULKS -- ACCESS PANELS

May 4, 2009

## ROUND CONTROL DAMPER WITH 2" STAND OFF LOCKING QUADRANT



**MODEL PBD-20RS**  
**BALANCING DAMPER – ROUND**

DIA.			EACH
6"			XX.XX
8"			XX.XX
10"			XX.XX
12"			XX.XX
14"			XX.XX

### MANUAL OPERATOR WITH 2" STAND OFF

#### Standard Construction:

**Frame:** 8" (203.2 mm) long sleeve, 20 ga. galvanized steel.  
**Blades:** 18 ga. galvanized steel.  
**Axles:** 1/4" (6.4 mm) square plated steel.  
**Finish:** Mill galvanized.  
**Minimum Size:** 4" (101.6 mm) diameter  
**Maximum Size:** 20" (508 mm) diameter  
**Operator:** Locking quadrant

**Notes:**

- All dampers are fabricated 1/8" (3.2 mm) under listed size unless otherwise specified "actual or exact".
- Not recommended for motor operation.
- Maximum recommended velocity is 1500 FPM.

