

# TAYLOR-SEIDENBACH, INC.

FIBERGLASS PRODUCTS -- ROOFING AND INSULATION -- HVAC PRODUCTS  
 AIR FILTERS -- FIRE STOP CAULKS -- ACCESS PANELS

FAX (504) 486-7477

PHONE (504) 486-7474

10-6-2009



**Dow Building Solutions**

## Spray Foam System

FROTH-PAK™ FS Foam Insulation Kit and FROTH-PAK™ Foam Sealant Kit are two-component, quick-cure polyurethane foams that quickly expand to fill cavities and penetrations (2"/50 mm or greater) through walls, floors and plates for pipes, vents and wiring. FROTH-PAK FS has a flame spread index of 25 or less (Class 1), qualifying it as an effective insulation at maximum 2" (50 mm) thickness as well as an air sealant. FROTH-PAK Foam Sealant is ideal for air sealing smaller areas that do not require a flame spread rating of 25, e.g., as insulation might. In addition to blocking out air infiltration, FROTH-PAK products help seal out moisture, dust, smoke, outside noise and insects. Key areas to seal inside the home include penetrations, rim joists and band joists, stud wall cavities, ceilings/attics, crawl spaces and basements, floors above garages and bathtub framework.



<b>FP-12</b>	<b>\$xx.xx / KIT</b>	<b>STOCK</b>
<b>FP-180</b>	<b>\$xx.xxx / KIT</b>	<b>STOCK</b>
<b>FP-180 FS</b>	<b>\$xx.xxx / KIT</b>	<b>NON-STOCK</b>

	Theoretical Yield <sup>(2)</sup> , bd ft (m <sup>3</sup> )
FROTH-PAK™ 12	12 (.28)
FROTH-PAK™ 120	120 (.28)
FROTH-PAK™ 180	175 (.41)
FROTH-PAK™ 600	560 (1.32)